



VPLX.EX659 - Valves, Alarm

Valves, Alarm

[See General Information for Valves, Alarm](#)

VIKING CORP

EX659

210 INDUSTRIAL PARK DR
HASTINGS, MI 49058-9706 USA

Model J-1, 3, 4, 6, 8 inch. sizes rated for 300 psig.

Model J-1 4, 6 and 8 inch. sizes rated for 175 psig, for use with Refrigerated Area / Cold Storage Trim.

Model J-1 valve provided with Model C-1 retarding chamber.

Model F-2 water motor gong.

[Last Updated](#) on 2011-11-16

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2022 UL LLC"